


“UCAT” Heavy-Duty Label Unwinders

A label unwinder is what you need to manage your label supply rolls. From very inexpensive to very sophisticated, LABELMATE's family of Heavy-Duty “UCAT” Label Unwinders will keep your label production running smoothly. All LABELMATE Unwinders are bi-directional.

UCAT-S: This is the world's least expensive professional Unwinder. It is unpowered and has a trouble-free fixed brake. The UCAT-S accepts up to 300 mm (12”) diameter rolls and up to 155 mm (6”) width, 76mm (3”) cores.




The UCAT-S

UCAT-1: This is the classic LABELMATE Unwinder with Adjustable Speed-Proportional Braking.

Up to 300 mm (12”) diameter rolls and 155 mm (6”) width, 76mm (3”) cores. Optional 255 mm (10”) width roll diameter and a 25 mm to 101 mm (1” to 4”) Adjustable Core Holder are available. Please see the table of available models below.


UCAT-2: This powered Unwinder automatically tracks label usage and provides powered label feed at speeds up to 76cm /sec (30-ips). The **UCAT-2** accepts standard 76mm (3”) cores and rolls up to 300 mm (12”) in diameter. 255 mm (10”) width is available. It can also be used as a full-featured Label Rewinder without any special setup. LABELMATE's renowned "Constant Adjustable



The UCAT-2 St.

Torquetm control system allows precise adjustment of feed speeds and rewind torque. External STOP / RUN Input included.

UCAT-40: A powered Unwinder like the UCAT-2, but with an impressive 40 cm (16”) roll diameter capacity. Supplied with LABELMATE's 76 mm (3” dia. X 6.6” width) “Quick-Chuck”tm, the UCAT-40 gives you the ultimate label Unwinder for volume production.



All LABELMATE Products are industrial-quality, maintenance-free, and backed by a **5-Year Parts and Labor Limited Warranty**, the longest in the industry. Order a LABELMATE UCAT Unwinder to solve your label supply roll problems, today!

See Page 2 for available models and specifications.

FULL SIZE "UCAT" HEAVY-DUTY LABEL UNWINDERS – Note: No rewind function unless stated.

MODEL	ADD SUFFIX	DESCRIPTION	WIDTH	DIAMETER	SPEED
UCAT-S	(NONE)	Economy Label Unwinder. Fixed brake. For 76 mm (3") cores.	Up to 155 mm (6")	Up to 300 mm (12")	Same as printer speed
UCAT-1	STANDARD	Heavy-duty Unwinder for 76 mm* (3") cores. Adjustable "Speed-Proportional Frictionless Braking"™.			
	-1-INCH	UCAT-1 for 25 mm (1") diameter cores.	Up to 155 mm (6")	Up to 220 mm (8,6")	
	-CHUCK	UCAT-1 with 76 mm (3") diameter "Quick-Chuck"™ *	Up to 170 mm (6,5")	Up to 300 mm (12")	
	-10-INCHES	UCAT-1 for labels up to 255 mm (10") wide. 76 mm* (3") core.	Up to 255 mm (10")	Up to 300 mm (12")	
	-ACH	UCAT-1 with Adjustable Core Holder for core size 25 mm to 101 mm (1" to 4")	Up to 155 mm (6")	Up to 280 mm (11")	
UCAT-2	STANDARD	Heavy-duty Powered Unwinder for label rolls with 76 mm* (3") cores. Continuously adjustable feed rate. Control arm tracks label unwind usage and starts & stops automatically. Also rewinds.	Up to 155 mm (6")	Up to 300 mm (12")	
	-1-INCH	UCAT-2 for 25 mm (1") diameter cores.	Up to 155 mm (6")	Up to 220 mm (8,6")	
	-ACH	UCAT-2 Powered Unwinder with Adjustable Core Holder for any core size from 25 mm to 101 mm (1" to 4") in diameter.	Up to 155 mm (6")	Up to 280 mm (11")	
	-CHUCK	UCAT-2 with 76mm* (3") diameter "Quick-Chuck"™ *	Up to 170 mm (6,5")	Up to 300 mm (12")	
	-10-INCHES	UCAT-2 for labels up to 255 mm (10") wide. 76 mm* (3") core.	Up to 255 mm (10")	Up to 300 mm (12")	
UCAT-40 <i>The Ultimate Unwinder</i>	(NONE)	Heavy-duty 400 mm (16") Powered Unwinder with 76 mm* (3") diameter "Quick-Chuck"™. Continuously adjustable feed rate. Control arm tracks label usage and starts & stops automatically. Also rewinds. *	Up to 170 mm (6,5")	Up to 400 mm (16")	

* Standard, S, CHUCK and 10-Inches Models are available for 38-, 40-, 44-, 70-, 76- and 100 mm (CHUCK only) diameter cores. Specify when ordering.

Dimensions: 324H x 381W x 318D mm (12.75H x 15W x 12.5D"). UCAT-40: 457H x 381W x 457D mm (18H x 15W x 18D")

Base plate footprint: 180 x 370mm (7 x 15") or 180 x 280 mm (7 x 11")

Weight: 9 Kg (19.9lbs) to 1 3Kg (28lbs).

Power Requirements: UCAT-S & UCAT-1: No power required. Others: 220-240vac (120vac 60Hz 50va. Max. avail.)

Warranty: 5-Year Parts and Labor Limited Warranty, the longest in the industry. (One-Year Limited Warranty on included Power Supply Module.)

Specifications are subject to change without notice. DATAUCAT EUR.DOC 04/2006